

# SMC AUTO-LOCKING LITE ALLOY STEEL



A Lite Alloy steel carabiner featuring double or triple action gates. Easily opened with one hand, but once released, the gate closes to a fully locked position. The carabiner gate and sleeve are stainless steel for problem-free operation. An offset "D" shape provides a smooth transfer of the Munter hitch when used as a belay and has ample volume to clip in large diameter ropes and over the rails of most litters.

### Key Features:

Lite Alloy Steel Body • Stainless Steel spring, pin and sleeve

Width: 2.76" (7.0 cm) » Length: 4.52" (11.5 cm) » Major Axis MBS: 45 kN (10116 lbf) »  
Minor Axis MBS: 12 kN (2697 lbf) » Gate Open MBS: 11 kN (2473 lbf) »  
Gate Opening: 0.88" (22.4 mm) » Weight: 7.0 oz (199 g)

DualGuard  
TriGuard

SM102200N  
SM102300N

★ USA MADE ★ BERRY COMPLIANT CERTIFIED NFPA 1983 (2012), G



Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)

A large, empty rectangular box with a thin black border, intended for handwritten notes or additional information.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)